

EXPLORE THE DURASTAR

STRENGTH

GCW

66,000 lbs.

GVW

23,500 - 44,600 lbs.

CONFIGURATIONS

AXLE CONFIGURATIONS

4x2 SBA

6x4 SBA

CAB INTERIOR TRIM LEVELS

Deluxe

Premium

CAB/SLEEPER CONFIGURATIONS

Day Cab

Extended Cab

Crew Cab

14500,E4500: 107" BBC, 40" BA

WHEELBASE OPTIONS

128 - 254"

DRIVETRAIN

ENGINES

Cummins® B6.7:

200 hp, 520 lb.-ft. torque, up to 325 hp, 750 lb.-ft. torque

Cummins® L9:

Up to 350 hp, 1,000 lb.-ft. torque

EXHAUST SYSTEM

Single, Horizontal, After-treatment Device Frame Mounted Right or Left Side,

Back of Cab, Horizontal or Vertical Tailpipe

Switchback After-treatment Device Mounted Right Side Under Cab, Horizontal or Vertical Tailpipe

Horizontal After-treatment Device Mounted In-line, Back of Cab, Horizontal Tailpipe

FRAME RAILS

Clean CA available for body mounting

Heat-Treated Alloy Steel

120.000 PSI

High Strength Low-Alloy Steel

50,000 - 80,000 PSI

FRONT AXLES

Dana Spicer:

8,000 - 14,000 lbs.

Meritor:

8,000 - 14,600 lbs.

FRONT SUSPENSIONS

Spring Parabolic Taper Leaf:

8,000-14,600 lbs.

REAR AXLES

Single (4x2)

Meritor: 13,500 - 30,000 lbs.

Dana Spicer: 13,500 - 30,000 lbs.

Tandem (6x4)

Meritor: 34,000 - 40,000 lbs.

Dana Spicer: 34,000 - 40,000 lbs.

REAR SUSPENSIONS

IROS Air Suspension Available for Single and Tandem Axle

Spring Single VariRate:

15,500 - 23,000 lbs.

Tandem, 4-Spring Multileaf:

34,000 lbs. (6x4)

TRANSMISSIONS

Allison:

1000, 2000, 3000 Series (HS, EVS, RDS) Automatic

Allison:

3000 TRV Series Automatic

Eaton® Fuller:

6-, 10-speed manual

Eaton® Procision:

7 speed Dual Clutch Automatic

OTHER COMPONENTS

ALTERNATORS

12 Volt 160-320 amp

BATTERY SYSTEMS

12 Volt, 2 to 3 batteries

BRAKES

Hydraulic Disc With Four Channel ABS

Air Brakes With ABS

ELECTRICAL SYSTEM

Diamond Logic® Electrical System

FUEL TANKS

40 - 140 Gallon Non Polished and Polished Aluminum

HEADLIGHTS

Long Life Halogen

STEERING

TRW/Ross Power

Sheppard Power

EXPLORE THE DURASTAR

CONNECT











CONTACT US