

Specification 43 21 00.01
HDPE Pipe floats and cable tethers
See Contract WD-2825R Plan C4-01

PF16-400-R

Optional
Attachment of cable, Hose,
Safety Lights or safety Flags

Locking Pins
for Easy Installation

Stack-n-Lock™
Allow Safe and Secure Stacking

Handholds for
Ergonomic Handling


44" [111.8cm]

44" [111.8cm]

Clamp Tite™ Inserts
Prevent Float from Slipping

EzGlide™
Tapered Inside and Outside Ends

Weight with Hardware: 146 Lbs.
Capacity at 50% Submergence: 765 Lbs.

| | |
|---|------------------------|
|  | NOT TO SCALE DRAWING |
| | Part NO. PF16-400-R |
| Features: Handholds for Ergonomic Handling Clamp Tite™ for Holding Pipe Locking Pins for Easy Installation Optional Safety Flag Attachment | |
| PATENTS PENDING | |
| DOCUMENT REVISION 08-21-2015 | |

PROPERTY OF NEPTUNE FLOTATION
101 W. 103rd STREET, INH 3360
INDIANAPOLIS, IN 46290 USA
Tel (317) 588-3600
FAX (317) 588-3700
sales@pipefloat.com www.pipefloat.com

