

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
BROWNING MANUFACTURING DIVISION 15-TOOTH SPROCKET (1/2" PITCH, HARDENED STEEL, NO. 40 CHAIN, 3/4" BORE)	SPROCKET:15T,1/2" PITCH, HARDENED STEEL	SPROCKET:15T,1/2" PITCH,HARDENED STEEL,NO 40 CHAIN,3/4" BORE, STANDARD KEY	BROWNING MANUFACTURING DIV	H4015	2
BROWNING MANUFACTURING DIVISION 13-TOOTH SPROCKET (1/2" PITCH, HARDENED TEETH, NO. 40 CHAIN, 1" BORE)	SPROCKET:13T,1/2" PITCH, HARDENED TEETH	SPROCKET:13T,1/2" PITCH,HARDENED TEETH,NO 40 CHAIN,1" BORE, STANDARD KEY, 2 SET SCREWS	BROWNING MANUFACTURING DIV	H4013	1
ISOLATION COMPRESSION SPRING (7" OD, 8" LG, 7/8" DIA WIRE)	SPRING,COMPRESSION:7" OD,8" LG,ISOLATION	SPRING,COMPRESSION:7" OD,8" LG,ISOLATION,7/8" DIA WIRE,CONV SN23330	CARRIER VIBRATING EQUIP,INC	110444	4
EXAIR CORP. SUPER AIR NOZZLE, 3/8" FNPT CONNECTION, STAINLESS STEEL	NOZZLE,AIR:3/8" FNPT CONNECTION,STAINLES	NOZZLE,AIR:3/8" FNPT CONNECTION,STAINLESS STEEL,SUPER AIR NOZZLE	EXAIR CORP.	1003	2
GARDNER DENVER AIR LOW-PRESSURE CYLINDER PISTON	PISTON: L.P CYLINDER,GARDNER-DENVER AIR	PISTON: L.P CYLINDER,GARDNER-DENVER AIR	GARDNER	ACR 15 &12F34	1
GARDNER PISTON BUSHING (6.25" X 3.5" X 4")	BUSHING:PISTON,6.25" X 3.5" X 4", GARDNER	BUSHING:PISTON,6.25" X 3.5" X 4", GARDNER	GARDNER	12F54	4
GARDNER DENVER COMPRESSOR PISTON	PIN: PISTON,GARDNER-DENVER COMPRESSOR,MO	PIN: PISTON,GARDNER-DENVER COMPRESSOR,MO	GARDNER	62F23	4
GARDNER DENVER HIGH-PRESSURE CYLINDER PISTON	PISTON: H.P CYLINDER,FOR GARDNER-DENVER	PISTON: H.P CYLINDER,FOR GARDNER-DENVER	GARDNER	ABR15 &12F34	2
Gardner-Denver Valve Disc	DISC,VALVE:200 LB,GARDNER DENVER,MODEL:A	DISC,VALVE:200 LB,GARDNER DENVER,MODEL:A	GARDNER	1VB4267	3
GARDNER DENVER UNLOADER PLUNGER SEAL	SEAL: UNLOADER PLUNGER, GARDNER-DENVER,MO	SEAL: UNLOADER PLUNGER,GARDNER-DENVER,MO	GARDNER	60DD5	3
GARDNER-DENVER LP SUCTION VALVE CAGE	CAGE,VALVE:LP SUCTION VLV, GARDNER-DENVER	CAGE,VALVE:LP SUCTION VLV,GARDNER-DENVER	GARDNER	6VB42194	1
GARDNER-DENVER LP DISCHARGE VALVE CAGE	CAGE,VALVE:LP DISCHARGE VLV, GARDNER-DENV	CAGE,VALVE:LP DISCHARGE VLV,GARDNER-DENV	GARDNER	6VB42452	1
GARDNER-DENVER DISCHARGE VALVE COVER	COVER:DISCHARGE VALVE, GARDNER-DENVER,MOD	COVER:DISCHARGE VALVE,GARDNER-DENVER,MOD	GARDNER	2VB42185	1
GARDNER-DENVER DISCHARGE VALVE COVE	COVER:DISCHARGE VALVE, GARDNER-DENVER,MOD	COVER:DISCHARGE VALVE,GARDNER-DENVER,MOD	GARDNER	ABL 11	1
GARDNER DENVER SUCTION VALVE ASSEMBLY	ASSEMBLY:H.P. SUCTION VALVE, GARDNER-DENV	ASSEMBLY:H.P. SUCTION VALVE,GARDNER-DENV	GARDNER	2ABL563	2
GARDNER-DENVER HP SUCTION VALVE CAGE	CAGE,VALVE:HP SUCTION VLV, GARDNER-DENVER	CAGE,VALVE:HP SUCTION VLV,GARDNER-DENVER	GARDNER	ABL194	1
GARDNER-DENVER SUCTION VALVE COVER FOR AVSAR MODEL	COVER:SUCTION,GARDNER-DENVER,MODEL:AVSAR	COVER:SUCTION,GARDNER-DENVER,MODEL:AVSAR	GARDNER	ABL185	1
GARDNER-DENVER HP DISCHARGE VALVE CAGE	CAGE,VALVE:HP DISCHARGE VLV, GARDNER-DENV	CAGE,VALVE:HP DISCHARGE VLV,GARDNER-DENV	GARDNER	1ABL194	1
GARDNER-DENVER COMPRESSOR CRANKSHAFT	CRANKSHAFT:COMPRESSOR, GARDNER-DENVER COM	CRANKSHAFT:COMPRESSOR,GARDNER-DENVER COM	GARDNER DENVER WTR JETTING SYS	200AVS004	1
GARDNER DENVER WATER JETTING SYSTEMS COMPRESSOR SPRING	PIN: SPRING,GARDNER-DENVER COMPRESSOR,MO	PIN: SPRING,GARDNER-DENVER COMPRESSOR,MO	GARDNER DENVER WTR JETTING SYS	62R3	1
GARDNER DENVER WATER JETTING SYSTEMS HIGH-PRESSURE PISTON ROD	PIN: H.P PISTON ROD,GARDNER-DENVER,MODEL	PIN: H.P PISTON ROD,GARDNER-DENVER,MODEL	GARDNER DENVER WTR JETTING SYS	62F24	5
GARDNER DENVER LP SUCTION GUARD	GUARD:LP SUCTION,GARDNER-DENVER AIR COMP	GUARD:LP SUCTION,GARDNER-DENVER AIR COMP	GARDNER DENVER WTR JETTING SYS	VB42164A	1
GARDNER DENVER LP SUCTION VALVE GUIDE	GUIDE,VALVE:LP SUCTION VLV, GARDNER-DENVE	GUIDE,VALVE:LP SUCTION VLV,GARDNER-DENVE	GARDNER DENVER WTR JETTING SYS	VB260	3
GARDNER DENVER L.P. SUCTION VALVE SCREW	SCREW: VALVE,L.P. SUCTION,REF: 4,GARDNER-	SCREW: VALVE,L.P. SUCTION,REF:4,GARDNER-	GARDNER DENVER WTR JETTING SYS	75K80	6
GARDNER DENVER WATER JETTING SYSTEMS LOW-PRESSURE UNLOADER FINGER	PIN: L.P UNLOADER FINGER, GARDNER-DENVER	PIN: L.P UNLOADER FINGER,GARDNER-DENVER	GARDNER DENVER WTR JETTING SYS	VB218	8
GARDNER DENVER HP SUCTION VALVE GUARD	GUARD: HP SUCTION VALVE, GARDNER-DENVER A	GUARD: HP SUCTION VALVE,GARDNER-DENVER A	GARDNER DENVER WTR JETTING SYS	ABL164X	3

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
Gardner-Denver Diaphragm Cover for AVS Model	COVER:DIAPHRAGM,GARDNER-DENVER,MODEL:AVS	COVER:DIAPHRAGM,GARDNER-DENVER,MODEL:AVS	GARDNER DENVER WTR JETTING SYS	1WAU274	1
GARDNER DENVER HP DISCHARGE GUARD	GUARD:HP DISCHARGE,GARDNER-DENVER AIR CO	GUARD:HP DISCHARGE,GARDNER-DENVER AIR CO	GARDNER DENVER WTR JETTING SYS	128	1
GARDNER-DENVER COMPRESSOR CRANKSHAFT	CRANKSHAFT:COMPRESSOR,FOR GARDNER-DENVER	CRANKSHAFT:COMPRESSOR,FOR GARDNER-DENVER	GARDNER DENVER WTR JETTING SYS	VAB-569	1
GATES MICRO-V POLY V-BELT 220J8	MICRO-V POLY:V-BELT, NO. 220J8. "J" SECT	MICRO-V POLY:V-BELT,NO. 220J8. "J" SECTION, 22" LONG BELT WITH 8 RIBS.FOR USE ON REBLEND VACUUM BLOWERS.	GATES GmbH	917102208	6
GATES RUBBER CO. 2" MAIN RAM (HEAD) HYDRAULIC HOSE ASSEMBLY FOR BALERS A/B AND 500 A/B	HOSE,HYDRAULIC:2" D,5'-2" LG, SYNTHETIC R	HOSE,HYDRAULIC:2" D,5'-2" LG,SYNTHETIC RUBBER/INTERNAL WIRE, 32C13 SAE100R13,SERIES 306 BOTH ENDS,HIGH PRESSURE WIRE REINFORCED,ITEM:45,BALER 400A/B & 500A/B MAIN RAM (HEAD), BAYER DWG:D-38900 SHEET 1 & 2 ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### HOSE ASSEMBLY, 2" MAIN RAM (HEAD), BALERS A/B & 500 A/B, BAYER DWG #D-38900 SHT. 1 & 2, ITEM 45 FOR BALER, HYDRAULIC POWER UNIT, BASIC HYDRAULICS DWG NO 13-4171-1, 13-4171-2 SERVICE NO. HYD-400A	GATES RUBBER CO.	32PCM-32FL X#32PCM-32FL-62"	2
GE INDUSTRIAL SYSTEMS RACK COOLING FAN	FAN:RACK COOLING,115 VAC	FAN:RACK COOLING,115 VAC	GE INDUSTRIAL SYSTEMS	IC697ACC721	2
HACH CO. 2.5A 250V FUSE	FUSE:2.5 A,250 V,5 MM DIA,20 MM LG	FUSE:2.5 A,250 V,5 MM DIA,20 MM LG	HACH CO.	4952600	4
HACH CO. CLEAR PIPE FOR SAMPLE CONDITIONING SYSTEM, CHLORINE ANALYZER	PIPE:CLEAR,FOR SAMPLE CONDITIONING SYSTE	PIPE:CLEAR,FOR SAMPLE CONDITIONING SYSTEM,CHLORINE ANALYZER	HACH CO.	5417400	1
JM CLIPPER HEAT EXCHANGER GASKET	GASKET,HEAT EXCHANGER:SOLID, 39-1/2" OD,3	GASKET,HEAT EXCHANGER:SOLID,39-1/2" OD,38-1/2" ID,1/16" THK, SHELL CAP,GASKET MADE BY INFUSING A SEAMLESS LAYER OF FLEXIBLE GRAPHITE AT VARYING DENSITIES AND THICKNESS OVER A CORRUGATED METAL CORE OF 316 STAINLESS STEEL.DWG A03-38061-9 REV.B	JM CLIPPER	DYNAGRAPH	3
JOHN CRANE, INC. MECHANICAL SEAL 1-7/8" DIA SHAFT/SLEEVE, 88 STYLE	SEAL,MECHANICAL:1-7/8" DIA SHAFT/SLEEVE,	SEAL,MECHANICAL:1-7/8" DIA SHAFT/SLEEVE,88 STYLE,TANDEM ARRANGEMENT,BALANCED,TUNGSTEN CARBIDE STAT FACE, CARBON ROT FACE,316 SS HARDWARE,HASTELLOY C SPR,VITON SEC SEAL,#6160 FIBRE GSKT MAT,2.623" / 2.937" HOUSING/BORE DIA, CODE:XF-1015HC,DWG. CFSP 96911 ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### SEAL, CARTRIDGE, COMP. CRANE, CARTRIDGE, DOUBLE, SIZE 1-7/8", TYPE 88, CODE XF-1DHC, DWG. CFSP 96911 SERV. NO. PP337, P480 AND P150D	JOHN CRANE,INC	1-M41597	2
John Crane, Inc. Mechanical Seal 1-7/8" Dia Shaft/Sleeve, 88 Style	SEAL,MECHANICAL:1-7/8" DIA SHAFT/SLEEVE,	SEAL,MECHANICAL:1-7/8" DIA SHAFT/SLEEVE,88 STYLE,TANDEM ARRANGEMENT,BALANCED,TUNGSTEN CARBIDE STAT FACE, CARBON ROT FACE,316 SS HARDWARE,HASTELLOY C SPR,VITON SEC SEAL,#6160 FIBRE GSKT MAT,2.623" / 2.937" HOUSING/BORE DIA, CODE:XF-1015HC,DWG. CFSP 96911 ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### SEAL, CARTRIDGE, COMP. CRANE, CARTRIDGE, DOUBLE, SIZE 1-7/8", TYPE 88, CODE XF-1DHC, DWG. CFSP 96911 SERV. NO. PP337, P480 AND P150D	JOHN CRANE,INC	1-M41597	2
KINGSBURY PLAIN JOURNAL SHOE	SHOE,BEARING:THRUST,SHOE, PLAIN KINGSBURY	SHOE,BEARING:THRUST,SHOE,PLAIN KINGSBURY JOURNAL ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### SHOE, PLAIN KINGSBURY JOURNAL	KINGSBURY	475142-4	4
KINGSBURY JOURNAL SHOE	SHOE,BEARING:THRUST,SHOE, INST. JOURNAL	SHOE,BEARING:THRUST,SHOE,INST. JOURNAL ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### SHOE,INST. JOURNAL	KINGSBURY	371507-4	3

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
KTM PRODUCTS, INC. 2" #150 3-WAY BALL VALVE WITH PTFE PACKING	VALVE,BALL:2"#150,3-WAY 316 SS. PACKING M	VALVE,BALL:2"#150,3-WAY 316 SS.PACKING MATERIAL PTFE ELOMATIC ESA 200 A/ N4 RACK AND PINION ACTUATOR FAIL POSITION TO BE BOTTOM PORT OPEN TO RIGHT PORT WITH SOLENOID AND LIMIT SWITCHES SPARE 3 WAY MF/DF RX VALVE BUT WILL NEED TO REVIEW ORIENTATION DEPENDING ON WHICH REACTOR THIS GOES INTO:ON – OFF CONTROL ONLY,IN LEFT PORT MIXED FEED,IN BOTTOM PORT DILUTE FEED, OUT RIGHT PORT TO REACTOR, AIR FAILURE LEFT PORT CLOSED, BOTTOM PORT TO RIGHT PORT OPEN. SOLENOID VALVE DEENERGIZED VENTS ACTUATOR THIS SETUP FOR RX 2 AND RX 4, FOR RX 1 AND RX 3 SERVICE SWITCH MIRROR IMAGE.	KTM PRODUCTS,INC.	3900 TEE PORT	1
NFM/WELDING ENGINEERS INC. 18" HYDRAULIC HOSE ASSEMBLY	HOSE,HYDRAULIC:18" LG, HYDRAULIC HOSE COM	HOSE,HYDRAULIC:18" LG,HYDRAULIC HOSE COMPLETE WITH 1A24FLB24 FITTINGS BOTH ENDS(FITTINGS:180 DEG. OFFSET FROM EACH OTHER)FOR OIL PUMP:ETP-1055 ON WELDING ENGINEERS 1:1 GEAR BOX (P-404) ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### HOSE, HYDRAULIC. TANK WAGON - 24. 18 INCHES OF HOSE COMPLETE WITH 1A24FLB24 FITTINGS BOTH ENDS. (FITTINGS - 180 DEG. OFF SET FROM EACH OTHER). FOR OIL PUMP #ETP-1055, FOR WELDING ENGINEERS 1:1 GEAR BOX (P-404)	NFM/WELDING ENGINEERS INC.	*	1
NOPAK CORPORATION PNEUMATIC LINEAR ACTUATING CYLINDER	CYLINDER,LINEAR ACTUATING: PNEUMATIC,3" B	CYLINDER,LINEAR ACTUATING:PNEUMATIC,3" BORE BORE,15" STROKE,NOPAK CYLINDER,LINEAR ACTUATING:PNEUMATIC,3" BORE BORE,15" STROKE,NOPAKAIR CYLINDER,CLASS:1 AIR CYLINDER, CLASS:1 ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES### ### CYLINDER PRESS AIR, NOPAK,CLASS 1,3" X 15",XA-SSOB1- "C" DIA.,2 1/CYLINDER PRESS AIR, NOPAK,CLASS 1,3" X 15",XA-SSOB1- "C" DIA.,2 1/8" FULLY THREADED EACH END,TOTAL LENGTH TO BE 42 1/4",FOR HYDRAUL 8" FULLY THREADED EACH END,TOTAL LENGTH TO BE 42 1/4",FOR HYDRAULIC BALING PRESS,CONSOLIDATED MACHINE,MDL #HCB-R1 (600), SERVICE #B IC BALING PRESS,CONSOLIDATED MACHINE,MDL #HCB-R1 (600),SERVICE #BA-400AA-400A	NOPAK CORP.	*	1
PARKER 1/2"D, 36" HYDRAULIC HOSE	HOSE,HYDRAULIC:1/2" D,36" LG, SAE 100R2 T	HOSE,HYDRAULIC:1/2" D,36" LG,SAE 100R2 TYPE AT,4250 PSI,FEMALE 37 DEG SWIVEL,SYNTHETIC FIBER BRAIDED WITH 2 BRAIDS HIGH TENSILE STEEL	PARKER	381-8 W/10643-6-8&13943-6-8	4
RUPTURE DISC	DISC,RUPTURE:4" D,70 PSIG @ 72 DEG F BUR	DISC,RUPTURE:4" D,70 PSIG @ 72 DEG F BURST PRESS,INCONEL 600, TYPE DISC,RUPTURE:4" D,70 PSIG @ 72 DEG F BURST PRESS, INCONEL 600,TYPEDV,MFG RANGE 66 PSIG MIN - 70 PSIG MAX,ASME CERTIFICATION: SECTI DV,MFG RANGE 66 PSIG MIN - 70 PSIG MAX, ASME CERTIFICATION: SECTI ON VIII & "UD" SYMBOL,MIN ORDER 3 ON VIII & "UD" SYMBOL,MIN ORDER 3. TAG#RD201/2/3/4/5-RD9202/3/4/5/7/12/13. VACCUUM SUPPORT RATED TO90 PSI.	PROCESS EQUIPMENT CORP.	D-V-026	9
TB WOODS 8.43" DIAMETER COUPLING HUB FOR COOLING TOWER JACKSHAFT	HUB,COUPLING:8.43" DIAMETER,3 3/8" BORE	HUB,COUPLING:8.43" DIAMETER,3 3/8" BORE WITH 7/8" X 7/16" KEYWAY,4 BOLT STAINLESS STEEL COUPLING HUB WITH 2 SET SCREWS, MOTOR HUB FOR COOLING TOWER JACKSHAFT	TB WOODS,INC	AJ45-3-3/8-E TBW	1
TB WOODS MODIFIED DRIVE SHAFT	SHAFT: DRIVE, FORMSPRAG A5-45 MODIFIED	SHAFT:DRIVE,FORMSPRAG A5-45 MODIFIED JACKSHAFT,304 SS,119 9/16" SHAFT:DRIVE,FORMSPRAG A5-45 MODIFIED JACKSHAFT,304 SS,119 9/16" LENGTH,A 8.43" DIAMETER,AJ45 4 BOLT SS COUPLING HUB WELDED ON EACH LENGTH,A 8.43" DIAMETER,AJ45 4 BOLT SS COUPLING HUB WELDED ON EACH END,BALANCED ASSEMBLY, SPECIFIC TO BUTYL COOLING TOWER CF-190 A,B AND C END, BALANCED ASSEMBLY,SPECIFIC TO BUTYL COOLING TOWER CF-190 A,B AND C DRIVES DRIVES DRIVE SHAFT, MODEL A5-45 MODIFIED, 304 SS., LENGTH 119-9/16", DRI DRIVE SHAFT, MODEL A5-45 MODIFIED, 304 SS., LENGTH 119-9/16", DRIVER BORE 3/3/8"WITH 7/8X7/16 KEYWAY. DRIVEN BORE 2.436" WITH 5/8X VER BORE 3/3/8" WITH 7/8X7/16 KEYWAY. DRIVEN BORE 2.436" WITH 5/8X5/16 KEYWAY, TO INCLUDE DISC PAC FOR GEAR BOX, AMARILLAA1311, 11 5/16 KEYWAY, TO INCLUDE DISC PAC FOR GEAR BOX, AMARILLAA1311, 11TO 1 RATIO (FOR CT-190 COOLING TOWER, 4-298) TO 1 RATIO (FOR CT-190 COOLING TOWER, 4-298)	TB WOODS,INC	*	1

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
TBV 3" FULL PORT CONTROL VALVE REPAIR KIT	KIT:REPAIR,FOR CONTROL VALVE 3" FP TBV	KIT:REPAIR,FOR CONTROL VALVE 3" FP TBV 2G,3" FULL PORT VALVE IN 150# OR 300#.KIT INCLUDES:1 - BORONIZED 316 SS BALL/SEAT ASSEMBLY,5- GRAPHOIL STEM SEALS,2 - GRAPHOIL SEAT BACK SEALS,1 - SPIRAL WOUND BODY GASKET,1 - 25% GLASS FILLED TFE THRUST BEARING,1- IOM	TBV	REPAIR KIT FOR 3" FP TBV 2G	4
TBV 3" Full Port Control Valve Soft Goods Repair Kit	KIT:REPAIR,SOFT GOODS 3" FP 2G EA,FITS A	KIT:REPAIR,SOFT GOODS 3" FP 2G EA,FITS A 3" FULL PORT VALVE IN 150# OR 300#.KIT INCLUDES:5 - GRAPHOIL STEM SEALS, 2 -GRAFOIL SEAT BACK SEALS,1 - SPIRAL WOUND BODY GASKET,1 - 25% GLASS FILLED TFE THRUST BEARING,1 IOM	TBV	REPAIR KIT SOFT GOODS 3" FP 2G	5
TREL OF SARNIA LTD TURBULATOR SHAFT SLEEVE	SLEEVE,TURBULATOR SHAFT: 7.050" LONG,3.13	SLEEVE,TURBULATOR SHAFT:7.050" LONG,3.132" O.D.,MATERIAL 316 SS,TUNGSTEN CARBIDE HARDFACING APPLIED TO 3.500" OF SLEEVE, PER DWG:D-00-38252-039	Trel of Sarnia Ltd	*	1
REXNORD/THOMAS 40610 COUPLING BOLT KIT		BOLT:KIT,FOR REXNORD/THOMAS 40610 COUPLI			1
COPPUS TURBINE SHAFT FOR C4 LUBE OIL SYSTEM		Turbine shaft, Coppus, for C4 lube oil system			2
ASME SA35 6" BALL VALVE		VALVE,BALL:6"F/F DIM 15.88",SS ASME SA35			2
JOHN CRANE MECHANICAL SEAL 2.375" / 2.625" DIA SHAFT/SLEEVE, 1 STYLE		SEAL,MECHANICAL:2.375" / 2.625" DIA SHAF T/SLEEVE,1 STYLE,SINGLE ARRANGEMENT,NON-BALANCED,TUNGSTEN CARBIDE STAT FACE,CARB ON ROT FACE,316 SS HARDWARE,316 SS SPR,V ITON SEC SEAL,VITON GSKT MAT,3.75" HOUSI NG/BORE DIA,CODE:XF-10151 ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF D ISCREPANCIES ### SEAL, CARTRIDGE, COMP FOR SEAL, CRANE, SIZE 2-5/8" (2.625), TY PE 1, CART. CODE XF-10151, DWG. FSP-2425 8, SERV.# P-211 A/B/C			4
JOHN CRANE MECHANICAL SEAL 3.250" DIA SHAFT/SLEEVE, 88 STYLE, TANDEM ARRANGEMENT		SEAL,MECHANICAL:3.250" DIA SHAFT/SLEEVE, 88 STYLE,TANDEM ARRANGEMENT,BALANCED,TUN GSTEN CARBIDE STAT FACE,CARBON ROT FACE, 316 SS HARDWARE,HASTELLOY C SPR,VITON SE C SEAL,#6160 FIBRE GSKT MAT,4.248" / 4.9 37" HOUSING/BORE DIA,CODE:XF55-1015HC # ## FOLLOWING CLARIFIES ABOVE. ADVISE PU RCHASER OF DISCREPANCIES ### SEAL, CART RIDGE, SIZE 3.250, TYPE 88 DUAL, CODE XF -1015HC FOR GREERCO MIXER, MDL 10TSPLM, S/N 3-05984-B SERV M333 12-2209			1
JOHN CRANE MECHANICAL SEAL 1.875" DIA SHAFT/SLEEVE, 5620-P STYLE		SEAL,MECHANICAL:1.875" DIA SHAFT/SLEEVE, 5620-P STYLE,DUAL CARTRIDGE ARRANGEMENT ,PUSHER DESIGN,TUNGSTEN CARBIDE STAT FAC E,LEADED BRONZE ROT FACE,316 SS HARDWAR E,HASTELLOY C276 SPRING,TFE PROPYLENE SE C SEAL,VITON GSKT MAT,3.625" HOUSING/BO RE DIA,FITS CBL REAR COVER,CODE X18 4 1 X18 015 H/X18 F55 1 X18 015H,JOHN CRANE DWG HSP-1031656-1			1
TBV 3" FULL PORT CONTROL VALVE REPAIR KIT	KIT:REPAIR,FOR CONTROL VALVE 3" FP TBV	KIT:REPAIR,FOR CONTROL VALVE 3" FP TBV 2G,3" FULL PORT VALVE IN 150# OR 300#.KIT INCLUDES:1 - BORONIZED 316 SS BALL/SEAT ASSEMBLY,5- GRAPHOIL STEM SEALS,2 - GRAPHOIL SEAT BACK SEALS,1 - SPIRAL WOUND BODY GASKET,1 - 25% GLASS FILLED TFE THRUST BEARING,1- IOM			4
TBV 3" FULL PORT CONTROL VALVE SOFT GOODS REPAIR KIT	KIT:REPAIR,SOFT GOODS 3" FP 2G EA,FITS A	KIT:REPAIR,SOFT GOODS 3" FP 2G EA,FITS A 3" FULL PORT VALVE IN 150# OR 300#.KIT INCLUDES:5 - GRAPHOIL STEM SEALS, 2 -GRAFOIL SEAT BACK SEALS,1 - SPIRAL WOUND BODY GASKET,1 - 25% GLASS FILLED TFE THRUST BEARING,1 IOM			5
TB Woods 8.43" Diameter Coupling Hub for Cooling Tower Jackshaft	HUB,COUPLING:8.43" DIAMETER,3 3/8" BORE	HUB,COUPLING:8.43" DIAMETER,3 3/8" BORE WITH 7/8" X 7/16" KEYWAY,4 BOLT STAINLESS STEEL COUPLING HUB WITH 2 SET SCREWS, MOTOR HUB FOR COOLING TOWER JACKSHAFT			1
ISOLATION COMPRESSION SPRING (7" OD, 8" LG, 7/8" DIA WIRE)	SPRING,COMPRESSION:7" OD,8" LG,ISOLATION	SPRING,COMPRESSION:7" OD,8" LG,ISOLATION,7/8" DIA WIRE,CONV SN23330			4

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
HYDRAULIC HOSE ASSEMBLY FOR OIL PUMP ETP-1055 ON WELDING ENGINEERS 1:1 GEAR BOX (P-404)	HOSE, HYDRAULIC: 18" LG, HYDRAULIC HOSE COM	HOSE, HYDRAULIC: 18" LG, HYDRAULIC HOSE COMPLETE WITH 1A24FLB24 FITTINGS BOTH ENDS (FITTINGS: 180 DEG. OFFSET FROM EACH OTHER) FOR OIL PUMP: ETP-1055 ON WELDING ENGINEERS 1:1 GEAR BOX (P-404) ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### HOSE, HYDRAULIC. TANK WAGON - 24. 18 INCHES OF HOSE COMPLETE WITH 1A24FLB24 FITTINGS BOTH ENDS. (FITTINGS - 180 DEG. OFF SET FROM EACH OTHER). FOR OIL PUMP #ETP-1055, FOR WELDING ENGINEERS 1:1 GEAR BOX (P-404)			1
1/2" D, 36" HYDRAULIC HOSE WITH SAE 100R2 TYPE AT MATERIAL	HOSE, HYDRAULIC: 1/2" D, 36" LG, SAE 100R2 T	HOSE, HYDRAULIC: 1/2" D, 36" LG, SAE 100R2 TYPE AT, 4250 PSI, FEMALE 37 DEG SWIVEL, SYNTHETIC FIBER BRAIDED WITH 2 BRAIDS HIGH TENSILE STEEL			4
HEAT EXCHANGER GASKET	GASKET, HEAT EXCHANGER: SOLID, 39-1/2" OD, 3	GASKET, HEAT EXCHANGER: SOLID, 39-1/2" OD, 38-1/2" ID, 1/16" THK, SHELL CAP, GASKET MADE BY INFUSING A SEAMLESS LAYER OF FLEXIBLE GRAPHITE AT VARYING DENSITIES AND THICKNESS OVER A CORRUGATED METAL CORE OF 316 STAINLESS STEEL. DWG A03-38061-9 REV.B			1
BROWNING MANUFACTURING DIVISION 15-TOOTH SPROCKET (1/2" PITCH, HARDENED STEEL, NO. 40 CHAIN, 3/4" BORE, STANDARD KEY)	SPROCKET: 15T, 1/2" PITCH, HARDENED STEEL	SPROCKET: 15T, 1/2" PITCH, HARDENED STEEL, NO 40 CHAIN, 3/4" BORE, STANDARD KEY			2
BROWNING MANUFACTURING DIVISION 13-TOOTH SPROCKET (1/2" PITCH, HARDENED TEETH, NO. 40 CHAIN, 1" BORE)	SPROCKET: 13T, 1/2" PITCH, HARDENED TEETH	SPROCKET: 13T, 1/2" PITCH, HARDENED TEETH, NO 40 CHAIN, 1" BORE, STANDARD KEY, 2 SET SCREWS			1
TBV SERIES 2G 3" 150# FULL PORT CONTROL BALL VALVE	VALVE: BALL, 3" 150# FULL PORT CONTROL TBV	VALVE: BALL, 3" 150# FULL PORT CONTROL TBV SERIES 2G. 2 PC BARSTOCK CONSTRUCTED CRYOGENIC BALL VALVE WITH 150# RF FLANGED CONNECTIONS, DUAL CERTIFIED 316L AND 316 STAINLESS STEEL BODY / END, 316 STAINLESS STEEL BALL, NITRONIC 50 STEM, METAL SEATS C/W GRAFOIL SEALS, 300 SS BOLTING, PREPARED FOR ACTUATION, GROUNDING SPRING, BORONIZED BALL / SEATS, CLASS V SHUTOFF. SPECIAL MACHINED FULL PORT VERSION. VALVE MUST BE UNIDIRECTIONAL WITH MARKING OF FLOW DIRECTION ON BODY OF VALVE, AND RELIEF HOLE IN UPSTREAM SIDE OF BALL FOR RELIEF OF CAVITY. ACTUATION PACKAGE INCLUDES: EDA-1600 DOUBLE ACTING ACTUATOR, MO-520 OVERRIDE, 67CFR FISHER AIR SET INCLUDES A LOCK OUT BY PINNED ARRANGEMENT IN THE BRACKET & COUPLING. SIEMENS MOORE VALVE POSITIONER, 4-20 MA DC 1/4 TURN NAMUR STYLE SHAFT END W/ 3-90 DEG CAMS, W/ 90 DEG BEACON INDICATOR, STD CAPACITY SPOOL VALVE ASSEMBLY (CV=0.3), STD TEMP (-40 F TO 185F, -40 C TO 85 C), SET OF 3 GAUGES, NO LIMIT SWITCHES, 4-20 MA DC FEEDBACK W/ SS FEEDBACK GEAR, FM/CSA/ATEX/CE.			1
MECHANICAL SEAL		SEAL, MECHANICAL: 0.875" DIA SHAFT/SLEEVE, T-5620P STYLE, CARTRIDGE ARRANGEMENT, CODE X14/X48F-1058HC, DWG FSP-25213-1 (A)			1
DALTEC SYSTEM FAN		FAN: SYSTEM, DALTEC, MODEL IE 17-50 DMW ARR. 8, CL. 30K, S/N 11-14351-1 (&2), HASTELOY C276 IMPELLER, MILD STEEL CASING, WITH 1/4" NATURAL RUBBER LINING, CASING SHALL BE INTERCHANGEABLE FOR 2 OUTLET POSITIONS, DRAIN AND INSPECTION DOORS INTERCHANGEABLE, STD PAINT ON EXTERNAL COMPONENTS. UPGRADED W/ MODIFIED BOLT-ON SIDE HOUSING PANELS FOR MULTIPLE ORIENTATION DISCHARGE			1
THRUST BEARING ASSEMBLY FOR ALLIS CHALMERS MODEL DH3M COMPRESSOR		BEARING: THRUST, C4 OOS, ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### THRUST COMPLETE, ITEM #556, PT#16-142-351-569 f/ ALLIS CHALMERS MODEL #DH3M SINGLE STAGE VERTICALLY SPLIT, SERVICE #C-4, **GEAR #12-1889, MOTOR #10-8042			1

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
TILT PAD BEARING ASSEMBLY FOR ALLIS CHALMERS MODEL DH3M COMPRESSOR		BEARING:TILT PAD,4-1/2" ID,COMPLETE UNIT ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### BEARING COMPRESSOR,INBOARD,COMPLETE,4.5 ID,ITEM #552,PT #16-136-000-365 f/ ALLIS CHALMERS MODEL #DH3M,SINGLE STAGE VERTICALLY SPLIT,SERVICE #C-4,**GEAR #12-1889,MOTOR #10-8042			1
ALLIS CHALMERS DH3M COMPRESSOR OUTBOARD BEARING SHOES		SHOE,BEARING:3" ID,OUTBOARD BEARING SHOES,CONSISTS OF: 3 SHOES (P/N:16-139-909-187)& 2 SHOES WITH RTD(P/N: 16-139-909-219) FOR ALLIS CHALMERS COMPRESSOR,MODEL:DH3M,S/N:C-2119 ### FOLLOWING CLARIFIES ABOVE. ADVISE PURCHASER OF DISCREPANCIES ### OUTBOARD BEARING SHOES, 3.0 I.D. (5 PER SET), CONSISTS OF: SHOES ITEM #553A, P/N 16-139-909-187 (3), SHOES WITH RTD ITEM 553C P/N 16-139-909-219 (2), S/N C-2119 FOR COMPRESSOR, ALLIS CHALMERS, MODEL DH3M SINGLE STAGE VERTICALLY SPLIT, SERVICE NO.C-4 NOTE: (GEAR NO. #12-1889). (MOTOR NO. #10-8042).			1
BRASS BACKED THRUST BEARING SHOES		SHOE,BEARING:THRUST,BRASS BACKED,ITEMS:5			1
FLEXIBLE SHAFT COUPLING		COUPLING,SHAFT:FLEXIBLE ,STOCK BORE,5.72			1
BAFFLE OIL INBOARD		BAFFLE:OIL INBOARD,9-1/4" DIA,BRONZE,ALL			1
ALLIS CHALMERS COMPRESSOR BUSHING		BUSHING:COMPRESSOR,ALLIS CHALMERS,MODEL:			2
BAFFLE OUTBOARD		BAFFLE:OUTBOARD,ALLIS CHALMERS,MODEL:DH3			1
BAFFLE COMPRESSOR FILLER PIECES		BAFFLE: COMPRESSOR,FILLER PIECES,ALLIS C			2
ALLIS CHALMERS COMPRESSOR TRAP BUSHING SEAL		SEAL: TRAP BUSHING,ALLIS CHALMERS COMPRE			1
ALLIS CHALMERS 3.505" ID SEAL RING		RING: SEAL,3.505" ID,SEAL RINGS,ALLIS CH			2
GARDNER DENVER IMPELLER SEAL		SEAL: IMPELLER,ITEM:329,RIGHT HAND,FOR A			1
Allis Chalmers Compressor Spacer		SPACER:COMPRESSOR,ITEM:330,FOR ALLIS CHA			3
O-RING: 7-1/2" ID, COMPRESSOR DUAL TO CASING		O-RING:7-1/2" ID,COMPRESSOR,DUAL TO CASI			1
O-RING: 6.75" ID, COMPRESSOR DUAL TO STATOR		O-RING:6.75" ID,COMPRESSOR, DUAL,TO STAT			2
O-RING: 11-1/2" ID, IMPELLER SEAL		O-RING:11-1/2" ID,IMPELLER SEAL O-RING,			2
O-RING: 4.5" ID, 4.75" OD, 0.120" WD, IMPELLER		O-RING:4.5" ID,4.75" OD,0.120" WD,IMPELL			2
O-RING: 2.437" ID, 2.625" OD, 0.094" WD, COUPLING		O-RING:2.437" ID,2.625" OD,0.094" WD,COU			2
O-RING: 2.187" ID, 2.375" OD, 0.094" WD, COUPLING		O-RING:2.187" ID,2.375" OD,0.094" WD,COU			2
O-RING: 15" ID, ADAPTER COMPRESSOR TO CASING		O-RING:15" ID,ADAPTER COMPRESSOR,TO CASI			2
O-RING: 4.75" ID, IMPELLER SEAL		O-RING:4.75" ID,IMPELLER SEAL O-RING, 4.			1
O-Ring: 13" ID, Adapter to Casing		O-RING:13" ID,ADAPTER TO CASING O-RING,			1
O-RING: 11" ID, STATOR TO CASING		O-RING:11" ID,STATOR TO CASING O-RING, 1			3
O-RING:37" ID,CASING END COVER O-RING, 3		O-RING:37" ID,CASING END COVER O-RING, 3			1
PACK: COUPLING DISC, DISC PACK CONSISTING		PACK:COUPLING DISC,DISC PACK CONSISTING			2
ALLIS CHALMERS COUPLING BOLT SET		SET:COUPLING BOLT,FOR ALLIS CHALMERS SIN			1
ALLIS CHALMERS IMPELLER EYE SEAL RING		RING: SEAL,IMPELLER EYE SEAL RINGS,ALLIS			2

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
ALLIS CHALMERS MD LEFT-HAND COMPRESSOR STATOR		STATOR:COMPRESSOR (LH),ALLIS CHALMERS MD			1
INBOARD BEARING SHOES		SHOE,BEARING:STEEL,INBOARD BEARING SHOES			1
STEEL BACKED THRUST BEARING SHOE		SHOE,BEARING:THRUST,STEEL BACKED,THRUST			1
LOW SPEED COUPLING		COUPLING:LOW SPEED,11.312" OD,26.750"LG			1
LIFTING RIG ASSEMBLY FOR DISCHARGE		TOOL:LIFTING RIG ASSEMBLY FOR DISCHARGE			1
SEAL IMPELLER TOOL FOR SEALON ALLIS-CHALMERS		TOOL:SEAL IMPELLER,FOR SEALON ALLIS-CHAL			1
FAN WHEEL WITH SHAFT	Fan Wheel with Shaft, Balanced	WHEEL:FAN,COMPLETE WITH SHAFT,BALANCED,			2
UNKNOWN		24-A01,KIT CONSISTS OF ITEMS 1 TO 10KIT			1
DRESSER RAND LABYRINTH SEAL PULLER KIT		KIT:LABYRINTH SEALS PULLER,DRESSER RAND			1
HYDRAULIC COUPLING		KIT:HYDRAULIC FIT,COUPLING,DRESSER RAND			1
DRESSER RAND HYDRAULIC FITTING KIT		KIT:HYDRAULIC FIT,COUPLING,DRESSER RAND			1
PLATE: EXCHANGER, NITRILE RUBBER, COMPLETE		PLATE:EXCHANGER,NITRILE RUBBER,COMPLETE			1
ELECTRICAL HEAVY-DUTY SAFETY SWITCH, 400A 240V, TYPE 3R RAINPROOF		SWITCH; ELECTRICAL, HEAVY DUTY SAFETY SWITCH, 400A 240V, TYPE 3R RAINPROOF		3HD225N	1
BROWN & BOGGS PRECISION GROUND SHEAR OVERHEAD DRIVE KNIFE		KNIFE: OVERHEAD DRIVE,HIGH CHROME/CARBON,ITEM:2 FOR BROWN & BOGGS PRECISION GROUND SHEAR,MODEL:549,S/N:13431			1
STILLING WELL FOR SPHERE 17		STILLING WELL FOR SPHERE 17			1
RUPTURE DISC		DISC,RUPTURE:4" D,70 PSIG @ 72 DEG F BUR			7
OLD C2 TRANSFORMER		Old C2 transformer (finalize plan following TA, will have one surplus)			1
MECHANICAL SEAL FOR 1-7/8" DIAMETER SHAFT/SLEEVE		SEAL,MECHANICAL:1-7/8" DIA SHAFT/SLEEVE,			2
ISOLATION SPRING (7" OD, 8" LG, 7/8" DIA WIRE)		SPRING,COMPRESSION:7" OD,8" LG,ISOLATION			4
ASME SA352 6" BALL VALVE		VALVE,BALL:6"F/F DIM 10.5",CS ASME SA352			1
BEARING PILLOW BLOCK		BEARING,PILLOW BLOCK:2-15/16" ID,SPHERIC (WRONG BOLT PATTERN ITEMS)			2
GE INDUSTRIAL SYSTEMS C20 ROTOR FOR D10R10S COMPRESSOR		C20 Rotor, D10R10S Rotor PN: 490-704-201			1
C20 BUNDLE INCLUDES THE FOLLOWING COMPONENTS: DISCHARGE SIDE DRIVE END BEARING SUCTION SIDE NON-DRIVE END BEARING THRUST BEARING ASSEMBLY TILT PAD BEARING ASSEMBLY		C20 Bundle, D10R10S Datum Bundle, C22-024-A01			1
SAFETY EDGE		EDGE:SAFETY,63" LG,ASTRAGAL SAFETY EDGE			1
SAFETY EDGE		EDGE:SAFETY,64" LONG,SENSING STRIP,ALUMINUM MOUNT			2
SAFETY EDGE		EDGE:SAFETY,67" LG,SAFETY CAT.3			4
SAFETY EDGE		EDGE:SAFETY,69" LG,SAFETY CAT.3			3
Horizontal Rotameter (0 to 24)		FLOWMETER:HORIZONTAL ROTAMETER,0 TO 24			2
GAUGE,PRESSURE:0 TO 6 BAR,4" DIAL,316L S		GAUGE,PRESSURE:0 TO 6 BAR,4" DIAL,316L S			2
EXCITER:VARISTOR PLATE WITH INTERMEDIATE		EXCITER:VARISTOR PLATE WITH INTERMEDIATE			1

Asset Name	Short Description	Long Description	Manufacturer	Manufacturer Part Number	QTY
DIODE:D789N, FOR 11000 HP MOTOR C-2		DIODE:D789N, FOR 11000 HP MOTOR C-2			1
CHOKE:ELECTRICAL,DC LINK REACTOR,FOR		CHOKE:ELECTRICAL,DC LINK REACTOR,FOR			1
THERMOMETER:BULB FILLED, RANGE 0 TO 100		THERMOMETER:BULB FILLED,RANGE 0 TO 100			1
HEATER,SPACE:ANTI CONDENSATION,120VAC,		HEATER,SPACE:ANTI CONDENSATION,120VAC,			1
CHOKE:ELECTRICAL,11000HP, DC LINK REACTO		CHOKE:ELECTRICAL,11000HP, DC LINK REACTO			1
BEARING,SLEEVE:SHELL TYPE,INSULATED "DE"		BEARING,SLEEVE:SHELL TYPE,INSULATED "DE"			1
BEARING,SLEEVE:SHELL TYPE,INSULATED "NDE"		BEARING,SLEEVE:SHELL TYPE,INSULATED "NDE"			1
SEAL,LABYRINTH:FLOATING, COMMON FOR DE A		SEAL,LABYRINTH:FLOATING, COMMON FOR DE A			8
SHIM SET, C2 COMPRESSOR, ASSORTED SHIMS.		SHIM SET, C2 COMPRESSOR, ASSORTED SHIMS.			1
SHIM SET, C2 MOTOR, ASSORTED SHIMS. STAI		SHIM SET, C2 MOTOR, ASSORTED SHIMS. STAI			1
SENSOR: PRESSURE STRIP FOR CRATE PRESS		SENSOR: PRESSURE STRIP FOR CRATE PRESS			3
SENSOR: PRESSURE STRIP FOR CRATE PRESS		SENSOR: PRESSURE STRIP FOR CRATE PRESS			3
SENSOR: PRESSURE STRIP FOR CRATE PRESS		SENSOR: PRESSURE STRIP FOR CRATE PRESS			3